

IN THE CLAIMS

Please amend claims 1-3, 5, 6, 9-12, 15-29 as follows (all pending claims are reproduced for the Examiner's convenience):

1. (Currently Amended) A semiconductor integrated circuit device comprising:
- a first semiconductor substrate, in which[[,]] a memory cell array including a plurality of nonvolatile semiconductor memory cells, a plurality of bit lines electrically connected to the memory cell array, a plurality of word lines electrically connected to the memory cell array, a plurality of input terminals, and a plurality of transfer gate transistors each having one end electrically connected to a corresponding one of the word lines and another end electrically connected to a corresponding ~~to~~ one of the input terminals, are provided; and
 - a second semiconductor substrate, in which, a plurality of output terminals electrically connected to the input terminals of the first semiconductor substrate, and a word line control circuit configured to control the word lines and electrically connected to the output terminals, are provided.
2. (Currently Amended) The device according to claim 1, wherein the second semiconductor substrate is stacked on the first semiconductor substrate.
3. (Currently Amended) The device according to claim 1, further comprising:
- a plurality of first semiconductor substrates, wherein the second semiconductor substrate is stacked on at least one of the plurality of first semiconductor substrates.
4. (Original) The device according to claim 1, further comprising:
- a first package which seals the first semiconductor substrate, the first package having a plurality of first terminals electrically connected to the input terminals of the first semiconductor substrate, the first terminals being provided on a side surface of the first package;
 - a second package which seals the second semiconductor substrate, the second package having a plurality of second terminals electrically connected to the output terminals of the second semiconductor substrate, the second terminals beings provided on a side surface of the second package; and
 - a plurality of wirings which electrically connects the first terminals of the first package

and the second terminals of the second package, the wirings being provided on the side surfaces of the first package and the second package.

5. (Currently Amended) The device according to claim 4, wherein the second package is stacked on a surface different from the side surface of the first package.

6. (Currently Amended) The device according to claim 4, further comprising:
a plurality of first packages,

wherein the second package is stacked on a surface different from the side surface of at least one of the first packages.

7. (Original) The device according to claim 4, further comprising:
a third package which seals the first package, the second package and the wirings.

8. (Original) The device according to claim 6, further comprising:
a third package which seals the first packages, the second packages and the wirings.

9. (Currently Amended) A semiconductor integrated circuit device comprising:
a first semiconductor substrate, in which[[,]] a memory cell array including a plurality of nonvolatile semiconductor memory cells, a plurality of bit lines electrically connected to the memory cell array, a plurality of word lines electrically connected to the memory cell array, a plurality of input terminals, and a plurality of transfer gate transistors each having one end electrically connected to a corresponding one of the word lines and another end electrically connected to a corresponding ~~to~~ one of the input terminals, are provided; and

a second semiconductor substrate, in which[[,]]a plurality of output terminals electrically connected to the input terminals of the first semiconductor substrate, and a word line control circuit configured to control the word lines and electrically connected to the output terminals, an interface circuit, and a plurality of interface terminals electrically connected to the interface circuit, are provided.

10. (Currently Amended) The device according to claim 9, further comprising:
a first package which seals the first semiconductor substrate, the first package having a plurality of first terminals electrically connected to the input terminals of the first semiconductor substrate, the first terminals being provided on a side surface of the first package,

cmf
Q4

a second package which seals the second semiconductor substrate, the second package having a plurality of second terminals electrically connected to the output terminals of the second semiconductor substrate, and a plurality of third terminals electrically connected to the interface terminals of the second semiconductor substrate, the second terminals being provided on a side surface of the second package opposite to a lamination surface ~~with~~ of the first package; and

a plurality of wirings which electrically connects the first terminals of the first package and the second terminals of the second package, the wirings being provided on the side surfaces of the first package and the second package.

11. (Currently Amended) The device according to claim 10, wherein the second package is stacked on a surface different from the side surface of the first package.

12. (Currently Amended) The device according to claim 10, further comprising:
a plurality of first packages,
wherein the second package is stacked on a surface different from the side surface of at least one of the first packages.

13. (Original) The device according to claim 10, further comprising:
a third package which seals the first package, the second package and the wiring, the third package having a plurality of fourth terminals electrically connected to the third terminals of the second package.

14. (Original) The device according to claim 12, further comprising:
a third package which seals the first packages, the second package and the wirings, the third package having a plurality of fourth terminals electrically connected to the third terminals of the second package.

15. (Currently Amended) A semiconductor integrated circuit device comprising:
a first semiconductor substrate, in which[[,]] a memory cell array including a plurality of nonvolatile semiconductor memory cells, a plurality of bit lines electrically connected to the memory cell array, a first shift register configured to control the bit lines, a plurality of word lines electrically connected to the memory cell array, a plurality of input terminals, a plurality of transfer gate transistors each having one end electrically connected to a corresponding one of the

word lines and another end electrically connected to a corresponding ~~to~~ one of the input terminals, and a second shift register configured to control the transfer gate transistors, are provided; and

a second semiconductor substrate, in which[[,]] a plurality of output terminals electrically connected to the input terminals of the first semiconductor substrate, and a word line control circuit configured to control the word lines and electrically connected to the output terminals, are provided.

16. (Currently Amended) The device according to claim 15, wherein the second semiconductor substrate is stacked on the first semiconductor substrate.

17. (Currently Amended) The device according to claim 15, further comprising:
a plurality of first semiconductor substrates, wherein the second semiconductor substrate is stacked on at least one of the plurality of first semiconductor substrates.

18. (Currently Amended) The device according to claim 15, wherein the second semiconductor substrate[[,]] ~~in which,~~ includes a storage circuit which stores an address of a ~~defected~~ defective memory cell in the memory cell array[[,]] ~~is provided.~~

19. (Currently Amended) A nonvolatile semiconductor memory ~~system~~ package comprising:

^{device}
a memory [↑]having a memory cell array including a plurality of nonvolatile semiconductor memory cells;

a control portion configured to control the memory;

a network interface connectable to a network;

a file management portion connected to the network interface configured to ~~manages~~ manage a ~~relation~~ relationship between a data file given from the network and an address of the memory cell array; and

a memory interface connected to the file management portion configured to convert a signal given from the network to a signal which is capable of being used at the control portion.

20. (Currently Amended) The ~~system~~ package according to claim 19, wherein the network interface corresponds to a transmission control protocol/internet protocol.

21. (Currently Amended) The ~~system~~ package according to claim 20, wherein the network interface is connectable to the network by using a file transfer protocol.

22. (Currently Amended) The ~~system~~ package according to claim 20, wherein the network interface is connectable to the network by using an anonymous file transfer protocol.

23. (Currently Amended) The ~~system~~ package according to claim 20, wherein the network interface is connectable to the network by using a point-to-point protocol.

24. (Currently Amended) A nonvolatile semiconductor memory device comprising:
a first semiconductor substrate, in which[[,]] a memory having a memory cell array including a plurality of nonvolatile semiconductor memory cells, is provided; and
a second semiconductor substrate, in which[[,]] a control portion configured to control the memory, a network interface connectable to a network, a file management portion connected to the network interface configured to ~~manages~~ manage a relation between a data file given from the network and an address of the memory cell array, and a memory interface connected to the file management portion configured to convert a signal given from the network to a signal which is capable of being used at the control portion, are provided.

25. (Currently Amended) The device according to claim 24, wherein the second semiconductor substrate is stacked on the first semiconductor substrate.

26. (Currently Amended) The device according to claim 24, further comprising:
a plurality of first semiconductor substrates, wherein the second semiconductor substrate is stacked on at least one of the plurality of first semiconductor substrates.

27. (Currently Amended) The device according to claim 24, further comprising:
a first package which seals the first semiconductor substrate, the first package having a plurality of first terminals electrically connected to the memory cell array, the first terminals being provided on a side surface of the first package; and

a second package which seals the second semiconductor substrate, the second package having a plurality of second terminals electrically connected to the memory interface, and a plurality of third terminals electrically connected to the network interface, the second terminals being provided on a side surface of the second package and the third terminals being provided on

a surface of the second package opposite to a lamination surface ~~with~~ of the first package;

a plurality of wirings which electrically connects the first terminals of the first package and the second terminals of the second package, the wirings being provided on the side surfaces of the first package and the second package.

28. (Currently Amended) The device according to claim 27, wherein the second package is stacked on a surface different from the side surface of the first package.

29. (Currently Amended) The device according to claim 27, further comprising:

a plurality of first packages,

wherein the second package is stacked on a surface different from the side surface of at least one of the first packages.

30. (Original) The device according to claim 27, further comprising:

a third package which seals the first package, the second package and the wiring, the third package having a plurality of fourth terminals electrically connected to the third terminals of the second package.

31. (Original) The device according to claim 29, further comprising:

a third package which seals the first packages, the second package and the wirings, the third package having a plurality of fourth terminals electrically connected to the third terminals of the second package.

Please add claims 32 and 33 as follows:

32. (New) The package according to claim 19, wherein the package works as a storage device for the equipment.

33. (New) The package according to claim 19, wherein the package is also connectable to equipment disconnected from the network.